



Start Spot

Integrated LED downlights



Start Spot range of integrated LED downlights combines high lumen efficacy with outstanding value. The range comes in both IP20 and IP65 with 3000K, 4000K and new 6500K options.

IP20 **Start Spot** is ideal for kitchens and living rooms with 30° tilt which allows you to place light exactly where you want it. The unique lens gives the product the highly desirable "halogen sparkle".

The IP65 **Start Spot** is ideal for bathrooms and suitable for zone 1. It is fixed and comes with a frosted lens and a large beam angle of 100° that will flood the room full of light.

The **Start Spot** range has an integrated LED driver, polycarbonate body and a low profile of 41mm making it ideal to fit into low ceiling voids.

Start Spot Integrated LED downlights

FEATURES:

- **NEW:** dimmable and dim to warm
- **NEW** improved lower profile of 41mm
- Integrated LED accent downlight with high lumen efficacy
- IP20 version available in tilt and with unique lens design
- IP65 version fixed with frosted lens
- Cut-out of 65-74mm allows direct replacement of most halogen spots installation on the market
- Energy class: A++, A+, A
- Low maintenance: 30,000 hours LED life expectancy
- LED technology provides energy efficient solution and reduced maintenance costs



IP20 Start Spot Tilt



IP65 Start Spot Fixed - Bathroom
Zone 1 Suitable



IP20 - Tilt



IP65 - Fixed



*Fixed Models / **Tilt models

Item Code	Description	Cut-Out Dimension (mm)	Bezel Dimension (mm)	Body Colour	IP Rating	Beam Angle (°)	Tiltability (°)	System Power consumption (W)	Luminaire lumen output (lm)	Efficacy (lm/W)	Lifetime (hrs)
Tilt - IP20											
0053543	START SPOT LED IP20 3000K	65-74	86	White	20	38	30	5	400	80	30,000
0053544	START SPOT LED IP20 4000K	65-74	86	White	20	38	30	5	450	84	30,000
NEW Dim											
0053583	START SPOT LED DIM IP20 3000K	65-74	86	White	20	38	30	5.5	400	73	30,000
0053584	START SPOT LED DIM IP20 4000K	65-74	86	White	20	38	30	5.5	420	76	30,000
Fixed - IP65											
0053545	START SPOT LED IP65 3000K	65-74	86	White	65	100	No	6.5	540	83	30,000
0053546	START SPOT LED IP65 4000K	65-74	86	White	65	100	No	6.5	580	89	30,000
0053569	START SPOT LED IP65 3000K 3PK	65-74	86	White	65	100	No	6.5	540	83	30,000
0053581	START SPOT LED IP65 4000K 3PK	65-74	86	White	65	100	No	6.5	580	89	30,000
NEW Dim											
0053586	START SPOT LED DIM 3000K IP65	65-74	86	White	65	100	No	7	540	77	30,000
0053587	START SPOT LED DIM 4000K IP65	65-74	86	White	65	100	No	7	580	83	30,000
NEW Fixed - IP65 - Dim to warm											
0053589	START SPOT LED IP65 DIM TO WARM	65-74	86	White	65	100	No	7	480	69	30,000

Photometric data



3,000K

4,000K

6,500K

Dim to Warm

Dimensions (mm)



www.feilosylvania.com

T: F:
Email:

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication, specifications and performance data are constantly changing. Current details should therefore be checked with Feilo Sylvania Europe Limited

by **FEILO SYLVANIA**