



Less maintenance, more performance

START Downlight IP44




Introducing the new START Downlight IP44 range, designed as an ideal replacement for CFL luminaires ranging from 150mm to 225mm cut outs. With an IP44 rating from the front of the fixture, the range is perfect for applications such as corridors, bathrooms, receptions and back of house areas.

The START Downlight delivers impressive performance with efficacy up to 100lm/W

(175mm, 4000K version) and high lumen output of up to 2325lm (225mm, 4000K version). With a 50,000 hour lifetime and 5 year warranty the START Downlight IP44 comes with the benefit of less maintenance. Additionally, the inclusion of a loop-in and loop-out facility and recess depth of less than 65mm provides a simple yet effective solution.

START Downlight IP44




Features

- A range of LED Downlights perfect for perfect for corridors, bathrooms, receptions and back of house areas
- High efficacy of up to 100lm/W
- High lumen packages of up to 2325lm for 225mm cut outs
- IP44 rating allows for installation in applicable wet zone areas
- Push dim DALI and 1-10V options available
- Incorporated with innovative SylSmart lighting control technology- SylSmart Standalone Room SSC - fully wireless, easy to install and program solution for meeting rooms, small offices and class rooms
- Shallow recess depth of < 65mm
- Can replace existing CFL downlights using 150, 175, 205 & 225mm ceiling cut outs
- 3 hour emergency pack available
- Loop in-Loop out facility with push fit terminal block for quick wiring
- White bezel (RAL9003)
- Available in Warm White (3000K) and Neutral White (4000K)
- Energy class: A++, A+, A
- Lifetime of 50,000 hours at L70

Product information

Code	Description	Cut Out	Correlated Colour Temperature (K)	Total Power Consumption (W)	Fixture Lumen (lm)	Luminaire Efficacy (lm/W)	Nominal Average Life (hours)
START Downlight IP44							
0030324	START Downlight 150 IP44 1100lm 830	150	3000	12	1100	92	50,000
0030325	START Downlight 150 IP44 1175lm 840	150	4000	12	1175	98	50,000
0030326	START Downlight 175 IP44 1425lm 830	175	3000	15	1425	95	50,000
0030327	START Downlight 175 IP44 1525lm 840	175	4000	15	1525	102	50,000
0030328	START Downlight 205 IP44 1950lm 830	205	3000	21	1950	93	50,000
0030329	START Downlight 205 IP44 2025lm 840	205	4000	21	2025	96	50,000
0030330	START Downlight 225 IP44 2275lm 830	225	3000	24	2275	95	50,000
0030331	START Downlight 225 IP44 2325lm 840	225	4000	24	2325	97	50,000
DALI							
0030332	START Downlight 150 IP44 DALI 1150lm 830	150	3000	12	1150	96	50,000
0030333	START Downlight 150 IP44 DALI 1160lm 840	150	4000	12	1160	97	50,000
0030334	START Downlight 175 IP44 DALI 1400lm 830	175	3000	15	1400	93	50,000
0030335	START Downlight 175 IP44 DALI 1475lm 840	175	4000	15	1475	98	50,000
0030336	START Downlight 205 IP44 DALI 1950lm 830	205	3000	20	1950	98	50,000
0030337	START Downlight 205 IP44 DALI 2000lm 840	205	4000	20	2000	100	50,000
0030338	START Downlight 225 IP44 DALI 2325lm 830	225	3000	23	2325	101	50,000
0030339	START Downlight 225 IP44 DALI 2350lm 840	225	4000	23	2350	102	50,000
1-10V							
0030340	START Downlight 150 IP44 1-10V 1150lm 830	150	3000	12	1150	96	50,000
0030341	START Downlight 150 IP44 1-10V 1175lm 840	150	4000	12	1175	98	50,000
0030342	START Downlight 175 IP44 1-10V 1400lm 830	175	3000	15	1400	100	50,000
0030343	START Downlight 175 IP44 1-10V 1425lm 840	175	4000	15	1425	95	50,000
0030344	START Downlight 205 IP44 1-10V 1950lm 830	205	3000	20	1950	98	50,000
0030345	START Downlight 205 IP44 1-10V 1975lm 840	205	4000	20	1975	99	50,000
0030346	START Downlight 225 IP44 1-10V 2325lm 830	225	3000	23	2325	101	50,000
0030347	START Downlight 225 IP44 1-10V 2350lm 840	225	4000	23	2350	102	50,000
SylSmart							
0030375	START Downlight 205 IP44 SSC01 1950lm 830	205	4000	20	1950	98	50,000
0030376	START Downlight 205 IP44 SSC01 2025lm 840	205	4000	20	2000	100	50,000


START Downlight IP44




Accessory

Code	Description
2691958	165~240 EMG Pack


Photometric Data




START Downlight 150
IP44 1100lm 830



START Downlight 175
IP44 1425lm 830






START Downlight 205 IP44
1950lm 830



START Downlight 225
IP44 2275lm 830

Dimensions (mm)



Additional Images



START Downlight IP44 Front
& Side



START Downlight IP44 Side



START Downlight IP44 Front



START Downlight IP44 Back



START Downlight IP44





Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication, specifications and performance data are constantly changing. Current details should therefore be checked with Feilo Sylvania Europe Limited.

Copyright Feilo Sylvania Europe Limited January 2019

sylvania-lighting.com

A Feilo Sylvania Company